

CORECASYS N1000

IEEE 802.11b/g/n 2.4GHz WIRELESS ACCESS POINT

Compliant with IEEE802.11b/g/n Port Gigabit (10/100/1000)
Greater coverage for home or office
Intelligent QoS technology for VoIP and multi-media applications
AP, Repeater, Client, Bridge
Multiple operating modes for most flexible deployments
IEEE 802.3af PoE supports easy installation for administrators

Ultimate Performance

CORE N1000 is 802.11n wireless AP that delivers incomparable wireless performance for your environment. This wireless AP delivers up to 5x faster speeds than 802.11g while staying backward compatible with 802.11g and 802.11b networks.

Enhanced Multimedia Support

CORE N1000 employed WMM (WiFi Multimedia) technology, enabling multimedia applications to secure the largest bandwidth share on a wireless network. Complying to the IEEE 802.11e WLAN QoS draft standard, this product will improve user' Internet experience from plain data transmission to rich multimedia enjoyment without waiting.

Multiple operating modes

CORE N1000 has a 4-in-1 design comprising of AP, Repeater, Client, Bridge operating modes to give greater flexibility for WLAN network deployments.

CORECASYS

- Wireless N (802.11b/g/n 300Mbps)
- RAM 64 รับโหลดหนัก
- PoE จ่ายไฟผ่านสาย LAN
- รองรับ 16 SSID
- รองรับ SNMP
- Client Isolation
- Hi-speed Web Interface



CORECASYS N1000

Product Description			
Draft IEEE 802.11b/g/n 2.4GHz WIRELESS ACCESS POINT			
Standard Compliance			
IEEE802.3u MDI / MDIX 10/100/1000 Fast Ethernet IEEE802.11b/g/n wireless LAN interface			
Radio			
Antenna	2 * detachable 3dBi dipole antennas (SMA-R)		
Output Power * Band edge exclusive (Controllable for different country regulations)	IEEE 802.11b: 20dBm @ 11Mbps	IEEE 802.11g: 20dBm @ 6Mbps	IEEE 802.11n: 23dBm @ HT20 21dBm @ HT40
Sensitivity	IEEE 802.11b: -91dBm @ 1Mbps	IEEE 802.11g -86dBm @ 6Mbps	IEEE 802.11n -86dBm @ HT20 -84dBm @ HT40
Operating Frequency	IEEE 802.11b/g ISM Band; 802.11gn 20MHz US, Canada: 2.412GHz ~ 2.462 GHz , EU: 2.412 GHz ~ 2.472 GHz		
	IEEE 802.11gn 40MHz Band US, Canada : 2.422GHz ~ 2.452GHz, EU : 2.422GHz ~ 2.462GHz		
Modulation	IEEE 802.11b (DSSS): CCK, DQPSK, DBPSK IEEE 802.11g/n (OFDM/DSSS): QAM-64, QAM-16, QPSK, BPSK		
Software Specification			
Operation Mode	AP, Repeater, Client, Bridge		
Security	<ul style="list-style-type: none"> • MAC address filtering through WLAN (support 128 account) • IEEE 802.1x security (EAP-TLS, EAP-TTLS, PEAP, EAP-SIM, -FAST, -AKA) • 64/128-bits WEP • Both WPA/WPA2 PSK & Enterprise support • Mixed WPA& WPA2 mode (support both WPA and WPA2 clients) 		
Management	<ul style="list-style-type: none"> • Telnet, FTP, SNMP, Password Changes, Firmware updates, Configuration Files • Embedded Web Configuration management • Command-line interface • Telnet support (Password-protected telnet access to internal configuration manager). • FTP/Web for firmware downloading and configuration backup and restore. • Telnet remote access support. • Built-in Diagnostic Tool • SNMP Management (v1, v2C, C3) 		
Physical Specification			
PCBA Dimension	113.5mm(L) x 85mm(W) x 17.26mm(H)		
Weight	<500g		
Environment Specification			
	Temperature (Ambient)	Humidity (non-condensing)	
Operating	0 ~ 50 °C	10 ~ 90%	
Storage	-30 ~70 °C	10 ~ 90%	
Warranty			
12 months			